



Technische gegevens		T600 (400V)	T600 (230V)	T600C2 (400V)	T650M (400V)	T700S (400V)	T700S (230V)	T700 (400V)	T1000 (400V)
Velgmaat	Inch	14 - 26	14 - 26	14 - 26	13 - 26	14 - 42	14 - 42	14 - 42	14 - 56
Wiel diameter	cm	160	160	160	138	230	230	230	250
Wiel breedte	cm	78	78	78	60	105	105	105	120
Wiel gewicht	kg	500	500	500	700	1600	1600	1600	2000
Klembereik spanklauw   max.	Inch / cm	27 Inch / 70 cm	27 Inch / 70 cm	27 Inch / 70 cm	26 Inch / 66 cm	43 inch / 114 cm	43 inch / 114 cm	43 inch / 114 cm	60 Inch / 154 cm
Klembereik spanklauw   min.	cm	11 cm	11 cm	11 cm	12 cm	11 cm	11 cm	11 cm	15 cm
Afdruk- of montagekracht	kg / kN	2500 kg / 24.515 kN	2500 kg / 24.515 kN	3000 kg / 29.418 kN	2500 kg / 24.515 kN	3300 kg / 32.360 kN	3300 kg / 32.360 kN	3300 kg / 32.360 kN	5000 kg / 49.031 kN
Bedrijfsdruk	Bar	170	170	200	170	200	200	200	250
Kracht hydraulische pomp	kW	1.5	1.5	2.2	1.1	2.2	2.2	2.2	4.0
Kracht E-motor draaibeweging	kW	2.2	1.5	2.4 - 3.0	1.1	2.2	2.2	2.4 - 3.0	3.4 - 4.0
Montagesnelheid, links+rechts	snelheid	1	1	2	1	1	1	2	2
Toeren per minuut	tpm	9	9	7 - 15	9	5	5	5 - 10	4 - 8
Automatische bewegingen	bewegingen	8	8	8	8	8	8	10	12
Voltage van bedieningsunit	Volt (DC)	24	24	24	24	24	24	24	24
Posities afdrukarm op slede	posities	2	2	3	3	2	2	traploos	1 ( traploos)
Gewicht	kg	580	580	600	540	775	775	800	1200
Geluidsniveau	dB	<= 70	<= 70	<= 70	<= 70	<= 70	<= 70	<= 70	<= 70
4 zelf-centrerende armen		✓	✓	✓	✓	✓	✓	✓	✓
2de hydraulische versnelling		-	-	-	-	-	-	-	✓
Klep voor stabiele werkdruk		✓	✓	✓	✓	✓	✓	✓	✓
Voltage	Volt	400	230	400	400	400	230	400	400
Fase	fase(n)	3	1	3	3	3	1	3	3
Frequentie	Hz	50	50	50	50	50	50	50	50
Afzekerwaarde	Ampère	16	16 - 20	20	10 - 16	16 - 20	25	20	25
Vloeroppervlak (L x B)	mm	1900x1580	1900x1580	1700x1350	1650x980	1900x1740	1900x1740	1880x1740	2200x1900