

TyreON



Vergelijking Truck Banden Wisselaars

		Verticaal	Ook 230V- 1Ph		Mobiel	Ook 230V- 1Ph			
Technische gegevens		T500 (400V)	T600 (400V)	T600C2 (400V)	T650M2 (400V)	T700S (400V)	T700 (400V)	T1000 (400V)	T2000 (400V)
Velgmaat	Inch	19 - 26	14 - 26	14 - 26	13 - 26	14 - 42	14 - 42	14 - 56	14 - 60
Wiel diameter	cm	Ø 140	Ø 160	Ø 160	Ø 138	Ø 230	Ø 230	Ø 250	Ø 260
Wiel breedte	cm	47	78	78	70	105	105	120	140
Wiel gewicht	kg	380	500	500	750	1600	1600	2000	2250
Klembereik spanklauw	cm	11 - 45	11 - 70	11 - 70	10 - 68.5	11 - 114	11 - 114	13.5 - 155	13.5 - 155
Afdruk kracht	Kg	3500	2500	3000	2500	3300	3300	5000 - (8000*)	5000 - (8000*)
Bedrijfsdruk	Bar	250	170	200	130	200	200	250	250
Hydraulische pomp	kW	3.3	1.5	2.2	1.1	2.2	2.2	3.3 - 4.0	3.3 - 4.0
Elektromotor draaibeweging	kW	-	2.2	2.4 - 3.0	1.5	2.2	3.3 - 4.0	3.3 - 4.0	3.3 - 4.0
Montagesnelheid L+R	snelheid(en)	1	1	2	1	1	2	2	2
Toeren per minuut	tpm	6	9	7 - 15	7	5	5 - 10	4 - 8	4 - 8
Automatische bewegingen	bewegingen	10	8	8	8	8	12	14	16
Voltage van bedieningsunit	Volt (DC)	-	24	24	24	24	24	24	24
Posities afdrukarm op slede	posities	2	2	3	3	2	traploos	1 - traploos	1 - traploos
Gewicht	kg	485	580	600	470	775	800	1300	1700
Geluidsniveau	dB(A)	55 - 70	55 - 70	55 - 70	40 - 65	55 - 70	55 - 70	65 - 85	65 - 85
4 zelf-centrerende armen		✓	✓	✓	✓	✓	✓	✓	✓
Centrale hydr. terugslagklep		✓	✓	✓	✓	✓	✓	✓	✓
Smeernippels		✓	✓	✓	✓	✓	✓	✓	✓
2de hydraulische versnelling*		-	-	-	-	-	-	✓(1450+2850rpm)	✓(1450+2850rpm)
Voltage	Volt	400V-3Ph	400V-3Ph	400V-3Ph	400V- 3Ph	400V- 3Ph	400V- 3Ph	400V- 3Ph	400V- 3Ph
Afzekerwaarde	Ampère	20	16	20	16	16 - 20	20	25	25
Vloeroppervlak (L x B)	cm	110 x 110	190 x 158	170 x 135	122 x 105	190 x 174	188 x 174	220 x 190	220 x 200