

# TyreON



## Truck Banden Wisselaars (Electrisch-Hydraulisch)

		T500	T600	T600C1	T600C2 2-Speed	T700S	T700 2-Speed	T1000 2-Speed	T2000 2-Speed
Velgmaat	<b>Inch</b>	19 - 26	14 - 26	14 - 26	14 - 26	14 - 42	14 - 42	14 - 56	14 - 60
Wiel diameter	<b>cm</b>	Ø 140	Ø 160	Ø 160	Ø 160	Ø 230	Ø 230	Ø 250	Ø 265
Wiel breedte	<b>cm</b>	47	78	85	78	105	105	120	145
Wiel gewicht	<b>kg</b>	380	500	500	500	1600	1600	2000	2250
Klembereik spanklauw	<b>cm</b>	11 - 45	11 - 70	9,5 - 70	11 - 70	11 - 114	11 - 114	13.5 - 155	13.5 - 155
Afdruk- montagekracht	<b>kg</b>	max. 3500	max. 3000	max. 3000	max. 3500	max. 4000	max. 4000	max. 8000	max. 8000
Bedrijfsdruk (max.)	<b>Bar</b>	250	170	130	200	200	200	250	250
Hydraulische pomp	<b>kW</b>	3.3	1.5	1.5	2.2	2.2	2.2	3.3 - 4.0	3.3 - 4.0
Elektromotor draaibeweging	<b>kW</b>	-	2.2	2.2	2.4 - 3.0	2.2	3.3 - 4.0	3.3 - 4.0	3.3 - 4.0
Montagesnelheid, L+R	<b>snelheid(en)</b>	1	1	1	2	1	2	2	2
Toeren per minuut	<b>tpm</b>	6	9	6	7 - 15	5	5 - 10	4 - 8	4 - 8
Automatische bewegingen	<b>bewegingen</b>	10	8	8	8	8	12	14	16
Voltage van bedieningsunit	<b>Volt (DC)</b>	-	24	24	24	24	24	24	24
Posities afdrukarm op slede	<b>posities</b>	2	2	2	3	2	Traploos	1-Traploos	1-Traploos
2de hydraulische versnelling		-	-	-	-	-	-	✓(1450+2850rpm)	✓(1450+2850rpm)
Voltage - fasen	<b>Volt</b>	400V-3Ph	400V-3Ph	400V-3Ph	400V-3Ph	400V-3Ph	400V-3Ph	400V-3Ph	400V-3Ph
Optioneel voltage	<b>230V-1Ph</b>		✓(order)	✓(order)		✓(order)			
Afzeker waarde	<b>Ampère</b>	C16A	16A	16A	C16A	C16A	20A	C20A	C20A
Vloeroppervlak	<b>cm</b>	110 x 110	189 x 157	189 x 142	170 x 135	190 x 174	188 x 174	220 x 190	220 x 200
		VOL HYDRAULISCH		COMPACT	COMPACT			VOL AUTOMATISCH	VOL AUTOMATISCH