



		Verticaal	Ook 230V		Mobiel	Ook 230V		
Technische gegevens		T500 (400V)	T600 (400V)	T600C2 (400V)	T650M2 (400V)	T700S (400V)	T700 (400V)	T1000 (400V)
Velgmaat	Inch	19 - 26	14 - 26	14 - 26	13 - 26	14 - 42	14 - 42	14 - 56
Wiel diameter	cm	Ø 140	Ø 160	Ø 160	Ø 138	Ø 230	Ø 230	Ø 250
Wiel breedte	cm	47	78	78	70	105	105	120
Wiel gewicht	kg	380	500	500	750	1600	1600	2000
Klembereik spanklauw (max.)	Inch - cm	18" - 45 cm	27" - 70 cm	27" - 70 cm	27" - 68.5 cm	43" - 114 cm	43" - 114 cm	60" - 154 cm
Klembereik spanklauw (min.)	cm	11 cm	11 cm	11 cm	10 cm	11 cm	11 cm	15 cm
Afdruk kracht	Kg / kN	3500 kg / 34.323kN	2500 kg / 24.515kN	3000 kg / 29.418kN	2500 kg / 24.515kN	3300 kg / 32.360kN	3300 kg / 32.360kN	5000kg / 49.031kN
Bedrijfsdruk	Bar	250	170	200	130	200	200	250
Hydraulische pomp	kW	3.3	1.5	2.2	1.1	2.2	2.2	4.0
Elektromotor draai beweging	kW	-	2.2	2.4 - 3.0	1.5	2.2	3.4 - 4.0	3.4 - 4.0
Montagesnelheid L+R	snelheid	1	1	2	1	1	2	2
Toeren per minuut	tpm	6	9	7 - 15	7	5	5 - 10	4 - 8
Automatische bewegingen	bewegingen	10	8	8	8	8	12	14
Voltage van bedieningsunit	Volt (DC)	-	24	24	24	24	24	24
Posities afdrukarm op slede	posities	2	2	3	3	2	traploos	1 - traploos
Gewicht	kg	485	580	600	470	775	800	1200
Geluidsniveau	dB	<= 70	<=70	<= 70	<= 70	<= 70	<= 70	<= 70
4 zelf-centrerende armen		✓	✓	✓	✓	✓	✓	✓
Centrale hydr. terugslagklep		✓	✓	✓	✓	✓	✓	✓
Smeernippels		✓	✓	✓	✓	✓	✓	✓
2de hydraulische versnelling		-	-	-	-	-	-	✓
Voltage	V	400V-3Ph	400V-3Ph	400V-3Ph	400V- 3Ph	400V- 3Ph	400V- 3Ph	400V- 3Ph
Afzekerwaarde	Ampère	20	16	20	16	16 - 20	20	25
Vloeroppervlak (L x B)	cm	110 x 110	190 x 158	170 x 135	122 x 105	190 x 174	188 x 174	220 x 190